

Date: _____

Job Name: _____

Location: _____

Purchaser: _____

Installer: _____

Submitted to: _____

**Compatibility**

For ductless systems. Compatible with all mini-splits, room ACs, window ACs, PTACs, and PTHPs using an infrared remote control with a display.

Power Source

Installation available using 24V–40VA step-down transformer.

Operating Voltage

5V–2A from 24V–40VA

Standby Average Power Consumption

<1W

Time to Enter Network Standby After User Interaction

<1 minute

Static Temperature Accuracy

< ± 1.0° F

Built-In Sensors

Temperature/Humidity

Storage

Temperature: –31° F to 113° F

Operating Temperature

23° F to 122° F

Operating Humidity

5% to 95%

Temperature Setpoint Limit

45° F to 90° F

Radio Parameter

Frequency Band : 2.412 to 2.484 GHz

Maximum Radio-Frequency power : 20 dBm

WLAN Standard : IEEE 802.11 b/g/n

WLAN Channel : 1-11

ProWarranty





Extended 5-year coverage with Automatic warranty registration, ensuring peace of mind and long-term protection for your customers.

Compatible with All Ductless AC Brands

**FUJITSU****SIEMENS****TOSHIBA****SAMSUNG****HITACHI****Honeywell**

& many more



→ What's in the Box?**Boldr Smart Controller****ProMount**
Hardwired Wall Mount
Requires 2-3/8" hole saw.**LiteMount**
Snap Wall Mount**LiteStand****Power cable****US, EU, AU plugs****PowerBrick****→ Product Dimensions**